

State-space model

[Derivation of Kalman filter](#)

[Nonlinear Kalman filter](#)

The state-space model is defined by the following pdfs

$$\underbrace{f(x_t|x_{t-1}, u_{t-1})}_{\text{prediction}} \quad \underbrace{f(y_t|x_t, u_t)}_{\text{filtration}}$$

For standard case (linearity, normality and known matrices M, N, A, B) these pdfs are generated by the equations

$$\begin{aligned}x_t &= Mx_{t-1} + Nu_{t-1} + w_t \\ y_t &= Ax_t + Bu_t + v_t\end{aligned}$$

where M, N, A, B are matrices, w_t and v_t white noises with covariance matrices r_w and r_v .

Estimation of the state x_t can be performed by Kalman filter

$$[\mathbf{x_t}, \mathbf{R_x}, \mathbf{y_t}] = \text{Kalman}(\mathbf{x_t}, \mathbf{y_t}, \mathbf{u_t}, \mathbf{M}, \mathbf{N}, \mathbf{F}, \mathbf{A}, \mathbf{B}, \mathbf{G}, \mathbf{R_w}, \mathbf{R_v}, \mathbf{R_x})$$

where $\mathbf{R_w}$, $\mathbf{R_v}$ and $\mathbf{R_x}$ are covariance matrices of prediction model, filtration model and state estimate.

[Program and its description](#)

[Back to Main](#)